

Model 2888 is a fully electronic floor scale with an ultra-low profile for easy loading. The optional portability frame features built-in casters and ramps that make it easy to move this compact scale almost anywhere.

2888 DECKMATE®

Floor Scales

Specifications

Platform Size	30 x 30 inches (762 x 762 mm)	36 x 36 inches (914 x 914 mm)	42 x 42 inches (1067 x 1067 mm)
Capacity	500 and 1000 lb (600 kg)	500, 1000, and 2500 lb (600 and 1500 kg)	1000 and 2500 lb (600 and 1500 kg)
Platform Height	1.5 inches (38 mm)	2 inches (51 mm)	2 inches (51 mm)
Material	Epoxy-painted carbon steel, 304 stainless steel, or 316 stainless steel		
Metrological Approval	NTEP Class III, 5000d (CC# 96-106A1); Measurement Canada (AM-5175, Rev. 1)		
Hazardous Area Approval	Factory Mutual approved load cell		

Features	Benefits
Rugged Construction	<ul style="list-style-type: none"> 100% end loading. Ideal for concentrated loads such as drum totes. Built-in overload stops integral to each load cell.
Low Profile	<ul style="list-style-type: none"> Requires less effort to place loads on the scale.
Hermetically Sealed, Stainless Steel Load Cells	<ul style="list-style-type: none"> Provides maximum protection in harsh environments.
Rocker Pin Suspension	<ul style="list-style-type: none"> Automatically centers the platform so that only vertical forces are transmitted to the load cells.
Optional Portability Frame	<ul style="list-style-type: none"> Compact, easily portable scale. Mounting bracket rotates 360° so that the indicator can be seen from any side of the scale.
Optional Ramps	<ul style="list-style-type: none"> Ramps on portable scale fold up to engage wheels. Setup is quick and easy.
Optional Stainless Steel Platform	<ul style="list-style-type: none"> Ideal for wet and extremely corrosive environments.



Static Scale



Portable Scale

Contact your local [METTLER TOLEDO](#) authorized distributor or sales office for more information.

Produced in a facility that is

