

IND 465 Smart+

Counting and Weighing Terminal

Specifications

Operating Temperature	-10°C to 40°C (14°F to 104°F)
Dimensions: Aluminum Die Cast	Footprint: 10.9" W x 7.9" D x 2.8" H Option Box: 10.9" W x 7.9" D x 1.4" H
Power	120 VAC, 47-63 Hz
Approvals	UL, 3101-1; CSA, C22.2 No 1010.1-92; NTEP No. 05-010
Resolution	Up to 300,000d
Standard Interface	One – RS232
Certification	NTEP, 10,000d

Options:

- Ethernet (This option is IP43 compliant only)
- Digital I/O
- USB (Slave)
- RS232
- RS422/485
- Internal Battery
- Analog 2nd Scale



Note: One communication option or one analog 2nd scale option only.

Features	Benefits
Water Resistant	■ IP65 compliant for wet or dust environments
Programmable Soft-Keys	■ The user can setup his scale to fit his procedure and not the other way around
Accumulation	■ For each lot and/or batch, a printout can be generated
Checkweighing	■ For over/under package checking. This application supports optional relay outputs
Filling	■ For manual filling this application provides the operator with an easy to read display
Internal Database	■ 1500 records can be stored in this scale and recalled by barcode or keypad
Multiple Templates	■ Besides a standard template up to 5 other templates can be stored in the scale and recalled individually by data interface
Freely Programmable User Prompting	■ A sequence of operations can be setup so the user is prompted to follow the steps being displayed
Programmable Information	■ An info-key allows display of programmable information such as time and date, % accuracy, article name, etc.
Custom Factor	■ Setup of a factor and a unit to measure volume, length, or square feet e.g. for yarn count or basis weight
Two Scale Counting	■ Allows for two scale counting with optional 2 nd scale interface

Contact your local **METTLER TOLEDO** authorized distributor or sales office for more information.