

**DIRECT THERMAL/
THERMAL TRANSFER
PRINTER**

EasyCoder™ **4420**

Benefits:

- **Unsurpassed Reliability**
Based on the proven design of other successful Intermec printers, the 4420 performs non-stop, delivering fast, reliable printing at an economical price.
- **Versatile**
High quality printing and a 112 mm (4.4") print width makes the 4420 ideal for a variety of applications.
- **Continuous Duty Cycle**
The 4420 is built for demanding, high volume, harsh printing environments where round-the-clock performance is required.
- **Unequaled Print Registration**
Intermec's exclusive PrecisionPrint™ technology offers incomparable image registration on a wide range of labeling applications.
- **IPL Compatibility**
The 4420 with IPL3™, Intermec's latest printer language, is backward compatible with earlier Intermec IPL™ printers.



Superior performance at an economical price distinguish the 4420 as a rugged, reliable, high-volume, continuous duty cycle printer not normally associated with high-end performance printers. Unlike many printers in this price range, the 4420, housed in an all-steel casing, is ideal for harsh or adverse environments. With 32-bit RISC processing and 20.32cm/sec (8")/second print speed, the 4420 is both fast in image formatting and time-to-first print.

Featuring a variety of options, this 203 dpi printer is easily configurable to suit your particular environment. The 4420 comes standard with bidirectional parallel and high speed RS-232 communications interfaces. Options such as full batch take

up with auto-peel, cutter, internal IBM Coax™ and Twinax™ adapters and internal ethernet interface are all available.

Originally introduced on the EasyCoder 3240, PrecisionPrint™ technology keeps the printed image within the tightest tolerance, whether printing in batch or on demand operation. Even on tough labels where problems with label registration show up immediately, as with oddly shaped or small labels or those labels with a preprint, the 4420 excels with this proven technology.

With robust performance, fast throughput and all-steel housing, the 4420 is built to take it in harsh, industrial, manufacturing, distribution and warehousing environments.

EasyCoder™ **4420****General**

Direct Thermal and Thermal Transfer Printer for self-adhesive label, ticket and tag applications. Auto-peel, full internal rewind and cutter optional

Model

EasyCoder 4420

Physical Characteristics

Depth: 43.82 cm (17.25")

Height: 41.91 cm (16.5")

Width: 24.8 cm (9.75")

Weigh: 19.35 kg (43 lbs.)

Print Specifications

Thermal Transfer and Direct Thermal Printing

Selectable Print Speeds:

5.08cm (2"), 7.62 cm (3"), 10.16 cm (4"), 12.70 cm (5"), 15.24 cm (6"), 17.78 cm (7"), or 20.32 cm (8") centimeters/inches per seconds

Resolution: 8 dots/mm (203 dots per inch)

Maximum Width: 112 mm (4.4")

Maximum Length: Unlimited

Element: 0.125mm (0.00492)

Media Specifications

Style: Roll-feed, die-cut, continuous or fanfold labels, tags, or tickets

Type: Plain paper thermal transfer or thermal sensitive papers

Maximum Media Width: 114 mm (4.5")

Minimum Media Width: 19 mm (.75")

Maximum Media Length: 1220 mm (48")

Minimum Media Length: 12.7 mm (.5")

Thickness: .08 mm to .3 mm (.0003 to .012")

Supply Roll Capacity: 152.4 m (6000" linear)

Ribbon Specifications –

Type: Wax, wax/resin, resin
Standard Widths: 5.38 cm (2.12"), 7.62 cm (3.0"), 10.41 cm (4.1"), 11.43 cm (4.5")
Length: 457 m (18,000")

Font Specifications

21 resident bit-mapped fonts (includes OCR-A and OCR-B), 3 resident outline fonts, supports user-defined fonts and graphics, supports True Type fonts

Language

IPL3™, Compressed Graphics, GLOBE™, Backward Compatibility with 86XX and IPL2™

Connectivity

Serial interface standard

IEEE 1284 Parallel standard

Internal Ethernet interface optional

Internal IBM Twinax or Coax interface optional

Microsoft® Windows

Intermec InterDriver™ standard
Windows 3.x, 9x, NT 4.0/5.0

Intermec ActiveX® controls standard
Windows 9x, NT 4.0/5.0

PrintSet™ printer configuration utility
Windows 3.x, 9x, NT 4.0/5.0

NetPilot™ + Thin Wizard™ network configuration utility (with optional Ethernet)

Windows 9x, Windows NT 4.0/5.0

Character Sets

Unicode, all single byte codepage, all doublebyte codepage

Code page 850, French, German, ISO 256 character, Italian, Kanji/Katakana (optional), Norwegian/Danish, Spanish, Swedish/Finnish, Swiss, UK ASCII, USA ASCII

Power Supply

110, 115, 200, 230 VAC;
50Hz to 60Hz

Environment

Operating Temperature:
4° to 40°C (40° to 104°F)

Storage Temperature:
0° to 70°C (32° to 120°F)

Humidity: 10 to 90% (non condensing)

Ventilation: Free air

Bar Code Symbolologies

Code 2 of 5, Codabar, Code 11, Code 39, Code 93, Code 128, HIBC, Interleaved 2 of 5, Postnet, UPC/EAN, JIS-ITF

2D: Code One, Code 16K, Code 49, DataMatrix, PDF417, QR Code

Regulatory Approvals

Complies with all FCC Part 15, Class A; CISPR 22 Class B; ICES-003 Class B; UL, CSA & TÜV-GS agency approved; CE, NOM & C-TIC

Options

Internal rewind with auto-peel, DRAM image expansion, 4MB Flash storage expansion, 16MB Flash storage expansion, cutter

**Where
Information
Gets Down
To Business™**

Internet • www.intermec.com **E-mail** • info@intermec.com **Telephone** • 800-347-2636 (toll free in N. Am.) **Service and Support** • 800-755-5505 (toll free in N. Am.)

North America ▶ Headquarters • 6001 36th Avenue West, Everett, WA 98203-9280, tel: 800-347-2636 (toll free in N. Am.), fax: 661-775-4440
Norand Mobile Systems Division • 550 2nd Street S.E., Cedar Rapids IA 52401, tel: 800-452-2757 (toll free in N. Am.), fax: 319-369-3453
Amtech Systems Division • 19111 Dallas Parkway, Suite 300, Dallas, TX 75287-3106, tel: 800-923-4824 (toll free in N. Am.), fax: 972-733-6699
Label Products & Supplies • tel: 800-227-9947 (toll free), 513-874-5882 (direct), fax: 800-227-1707 (toll free), 513-874-8487 (direct)

Europe / Middle East & Africa ▶ Sovereign House, Vastern Road, Reading, Berkshire, RG1 8BT United Kingdom, tel: 44-118-987-9400, fax: 44-118-987-9401

Asia Pacific / Latin America ▶ Hong Kong • 26-12 Shell Tower, Times Square, 1 Matheson Street, Causeway Bay, tel: 852-2574-9777, fax: 852-2574-9725
Singapore • #25-16 International Plaza, 10 Anson Road, 079903, tel: 65-324-8391, fax: 65-324-8393
Australia • 15 Stamford Road, Oakleigh Victoria 3166, tel: 61-3-9563-0000, fax: 61-3-9563-4000
South America and Mexico • 2572 White Road, Irvine, CA 92614, tel: 949-975-1905 Ext. 1939, fax: 949-975-1827

Worldwide Fax Document Retrieval Service • tel: 800-755-5505 (toll free in North America), 650-556-8447 (direct)

Copyright © 1999 Intermec Technologies Corporation. All rights reserved. All trademarks are the property of their respective owners. Contents subject to change. Printed in the U.S.A. #608371C 8/99